

# Intermediate Level Introduction to Computing at CARC

Second in a three-part series

Matthew Fricke

Version 0.1




# Goals


- 1) SLURM scheduler literacy
  - 2) Ability to employ embarrassingly parallel solutions
  - 3) Ability to employ coupled parallel solutions.
- 
- We wont cover file transfer, storage systems, module system, conda, PBS. (These are all covered in depth in the video tutorials)

# Agenda

- HPC and Parallelism
- HPC Schedulers
- SLURM
- Embarrassingly Parallel
  - SLURM Arrays
  - GNU Parallel
- Coupled Parallelism
- MPI with MPI



**GNUparallel**



**slurm**  
workload manager



**MPI**

We will have one 15 minute break. Opportunity to see the machine room.

Tuesday, February 2, 20XX

Sample Footer Text

# Logging into Hopper



First login to the Linux **workstation** in front of you.

Use your CARC username and password.

Jacob, Keven, Tannor, and Jose can help you login if you have trouble.

This is an “important step” so don’t let me move on until you have logged in

# Logging into Hopper



```
ssh vanilla@hopper.alliance.unm.edu
```

Should prompt you for a password...

Don't let me move on until you are able to login.

# Logging into Hopper

Welcome to Hopper

Be sure to review the "Acceptable Use" guidelines posted on the CARC website.

For assistance using this system email [help@carc.unm.edu](mailto:help@carc.unm.edu).

Tutorial videos can be accessed through the CARC website: Go to <http://carc.unm.edu>, select the "New Users" menu and then click "Introduction to Computing at CARC".

Warning: By default home directories are world readable. Use the `chmod` command to restrict access.

Don't forget to acknowledge CARC in publications, dissertations, theses and presentations that use CARC computational resources:

"We would like to thank the UNM Center for Advanced Research Computing, supported in part by the National Science Foundation, for providing the research computing resources used in this work."

Please send citations to [publications@carc.unm.edu](mailto:publications@carc.unm.edu).

There are three types of slurm partitions on Hopper:

- 1) General - this partition is accessible by all CARC users.
- 2) Condo - preemptable scavenger queue available to all condo users. Your job must use checkpointing to use this queue or you will lose any work you have done if it is preempted by the partition's owner.
- 3) Named partitions - these partitions are available to condo users working under the grant/lab/center that purchased the associated hardware.

Type "qgrok" to get the status of the partitions.

-----  
Last login: Wed Jul 27 17:46:13 2022 from 129.24.246.68  
mfricke@hopper:~ \$



VOTED **#1** SOFT DRINK OF THE 31<sup>ST</sup> CENTURY!



[vanilla@hopper ~]\$ qgrok

| queues  | free  | busy  | offline | jobs  | nodes | CPUs  | GPUs  |
|---------|-------|-------|---------|-------|-------|-------|-------|
| -----   | ----- | ----- | -----   | ----- | ----- | ----- | ----- |
| general | 1     | 9     | 0       | 7     | 10    | 320   | 0     |
| debug   | 2     | 0     | 0       | 0     | 2     | 64    | 0     |
| totals: | 1     | 9     | 0       | 7     | 10    | 320   | 0     |

mvanilla@hopper:~ \$ qgrok

| queues    | free  | busy  | offline | jobs  | nodes | CPUs  | GPUs  |
|-----------|-------|-------|---------|-------|-------|-------|-------|
| -----     | ----- | ----- | -----   | ----- | ----- | ----- | ----- |
| general   | 1     | 9     | 0       | 7     | 10    | 320   | 0     |
| debug     | 2     | 0     | 0       | 0     | 2     | 64    | 0     |
| condo     | 18    | 19    | 1       | 7     | 38    | 1216  | 8     |
| bugs      | 0     | 2     | 0       | 0     | 2     | 64    | 0     |
| pcnc      | 1     | 1     | 0       | 0     | 2     | 64    | 0     |
| pathogen  | 1     | 0     | 0       | 0     | 1     | 32    | 0     |
| tc        | 5     | 5     | 0       | 3     | 10    | 320   | 0     |
| gold      | 2     | 0     | 0       | 0     | 2     | 64    | 0     |
| fishgen   | 0     | 1     | 0       | 0     | 1     | 32    | 0     |
| neuro-hsc | 8     | 6     | 0       | 0     | 14    | 448   | 0     |
| cup-ecs   | 0     | 2     | 0       | 2     | 2     | 64    | 4     |
| tid       | 0     | 1     | 0       | 0     | 1     | 32    | 2     |
| biocomp   | 0     | 1     | 0       | 0     | 1     | 32    | 1     |
| chakra    | 1     | 0     | 0       | 0     | 1     | 32    | 1     |
| pna       | 0     | 0     | 1       | 0     | 1     | 32    | 0     |
| totals:   | 19    | 28    | 1       | 14    | 48    | 1536  | 8     |

```
vanilla@hopper:~ $ qgrok
```

| queues    | free  | busy  | offline | jobs  | nodes | CPUs  | GPUs  |
|-----------|-------|-------|---------|-------|-------|-------|-------|
| -----     | ----- | ----- | -----   | ----- | ----- | ----- | ----- |
| general   | 1     | 9     | 0       | 7     | 10    | 320   | 0     |
| debug     | 2     | 0     | 0       | 0     | 2     | 64    | 0     |
| condo     | 18    | 19    | 1       | 7     | 38    | 1216  | 8     |
| bugs      | 0     | 2     | 0       | 0     | 2     | 64    | 0     |
| pcnc      | 1     | 1     |         |       |       |       |       |
| pathogen  | 1     | 0     |         |       |       |       |       |
| tc        | 5     | 5     |         |       |       |       |       |
| gold      | 2     | 0     |         |       |       |       |       |
| fishgen   | 0     | 1     |         |       |       |       |       |
| neuro-hsc | 8     | 6     |         |       |       |       |       |
| cup-ecs   | 0     | 2     |         |       |       |       |       |
| tid       | 0     | 1     |         |       |       |       |       |
| biocomp   | 0     | 1     |         |       |       |       |       |
| chakra    | 1     | 0     |         |       |       |       |       |
| pna       | 0     | 0     |         |       |       |       |       |
| totals:   | 19    | 28    |         |       |       |       |       |

**Open partitions for use by  
everyone with a CARC account.**

**Purchased by the Office for the  
Vice President for Research.**

vanilla@hopper:~ \$ qgrok

| queues    | free  | busy  | offline | jobs  | nodes | CPUs  | GPUs  |
|-----------|-------|-------|---------|-------|-------|-------|-------|
| -----     | ----- | ----- | -----   | ----- | ----- | ----- | ----- |
| general   | 1     | 9     | 0       | 7     | 10    | 320   | 0     |
| debug     | 2     | 0     | 0       | 0     | 2     | 64    | 0     |
| condo     | 18    | 19    | 1       | 7     | 38    | 1216  | 8     |
| bugs      | 0     | 2     | 0       | 0     | 2     | 64    | 0     |
| pcnc      | 1     | 1     | 0       | 0     | 2     | 64    | 0     |
| pathogen  | 1     | 0     | 0       | 0     | 1     | 32    | 0     |
| tc        | 5     | 5     | 0       | 3     | 10    | 320   | 0     |
| gold      | 2     | 0     | 0       | 0     | 2     | 64    | 0     |
| fishgen   | 0     | 1     | 0       | 0     | 1     | 32    | 0     |
| neuro-hsc | 8     | 6     | 0       | 0     | 14    | 448   | 0     |
| cup-ecs   | 0     | 2     | 0       | 2     | 2     | 64    | 4     |
| tid       | 0     | 1     | 0       | 0     | 1     | 32    | 2     |
| biocomp   | 0     | 1     | 0       | 0     | 1     | 32    | 1     |
| chakra    | 1     | 0     | 0       | 0     | 1     | 32    | 1     |
| pna       | 0     | 0     | 1       | 0     | 1     | 32    | 0     |
| totals:   | 19    | 28    | 1       | 14    | 48    | 1536  | 8     |

```
vanilla@hopper:~ $ qgrok
```

| queues    | free  | busy  | offline | jobs  | nodes | CPUs  | GPUs  |
|-----------|-------|-------|---------|-------|-------|-------|-------|
| -----     | ----- | ----- | -----   | ----- | ----- | ----- | ----- |
| general   | 1     | 9     | 0       | 7     | 10    | 320   | 0     |
| debug     | 2     | 0     | 0       | 0     | 2     | 64    | 0     |
| condo     | 18    | 19    | 1       | 7     | 38    | 1216  | 8     |
| bugs      | 0     | 2     | 0       | 0     | 2     | 64    | 0     |
| pcnc      | 1     | 1     |         |       |       |       |       |
| pathogen  | 1     | 0     |         |       |       |       |       |
| tc        | 5     | 5     |         |       |       |       |       |
| gold      | 2     | 0     |         |       |       |       |       |
| fishgen   | 0     | 1     |         |       |       |       |       |
| neuro-hsc | 8     | 6     |         |       |       |       |       |
| cup-ecs   | 0     | 2     |         |       |       |       |       |
| tid       | 0     | 1     |         |       |       |       |       |
| biocomp   | 0     | 1     |         |       |       |       |       |
| chakra    | 1     | 0     |         |       |       |       |       |
| pna       | 0     | 0     |         |       |       |       |       |
| totals:   | 19    | 28    |         |       |       |       |       |

## Private partitions

- Reserved for use by the purchaser.
- Request access by emailing [support@carc.unm.edu](mailto:support@carc.unm.edu) and CC the partition owner.

```
mfricke@hopper:~ $ qgrok
```

| queues       | free      | busy      | offline  | jobs     | nodes     | CPUs        | GPUs     |
|--------------|-----------|-----------|----------|----------|-----------|-------------|----------|
| -----        | -----     | -----     | -----    | -----    | -----     | -----       | -----    |
| general      | 1         | 9         | 0        | 7        | 10        | 320         | 0        |
| debug        | 2         | 0         | 0        | 0        | 2         | 64          | 0        |
| <b>condo</b> | <b>18</b> | <b>19</b> | <b>1</b> | <b>7</b> | <b>38</b> | <b>1216</b> | <b>8</b> |
| bugs         | 0         | 2         | 0        | 0        | 2         | 64          | 0        |
| pcnc         | 1         | 1         |          |          |           |             |          |
| pathogen     | 1         | 0         |          |          |           |             |          |
| tc           | 5         | 5         |          |          |           |             |          |
| gold         | 2         | 0         |          |          |           |             |          |
| fishgen      | 0         | 1         |          |          |           |             |          |
| neuro-hsc    | 8         | 6         |          |          |           |             |          |
| cup-ecs      | 0         | 2         |          |          |           |             |          |
| tid          | 0         | 1         |          |          |           |             |          |
| biocomp      | 0         | 1         |          |          |           |             |          |
| chakra       | 1         | 0         |          |          |           |             |          |
| pna          | 0         | 0         |          |          |           |             |          |
| totals:      | 19        | 28        |          |          |           |             |          |

## Condo “scavenger” partition

- Allows you to use compute nodes purchased by another group that are currently idle.
- May be interrupted at any time if the owners start to use it.

[Home](#) [About ▼](#) [Research ▼](#) [Education & training ▼](#) [News & events ▼](#) [New users ▼](#) [Systems ▼](#) [User support ▼](#)  
[Contact us ▼](#) [Donate](#)

## Welcome to the Center for Advanced Research Computing

The UNM Center for Advanced Research Computing is the hub of computational research at UNM and one of the largest computing centers in the State of New Mexico. It is an interdisciplinary community that uses computational resources to create new research insights. The goal is to lead and grow the computational research community at UNM.

Get started at CARC

Create a help ticket

- CARC systems information
- CARC infrastructure
- Resource limits
- Storage and backup
- Export control
- JupyterHub cluster links
- System status and downtime
- System Usage by Principal Investigator

four years

**CARC launches new condo cluster**

# Hopper Configuration

| Queue:               | General  | Debug    | Condo    | Private                   |
|----------------------|----------|----------|----------|---------------------------|
| Number of Processors | 64       | 8        | 192      | Determined by queue owner |
| Number of Nodes      | 2        | 2        | 6        |                           |
| Processors per Node  | 32       | 8        | 32       |                           |
| Walltime(H:M:S)      | 48:00:00 | 04:00:00 | 48:00:00 |                           |

```
[vanilla@hopper ~]$ sinfo --partition debug
PARTITION AVAIL  TIMELIMIT  NODES  STATE NODELIST
debug      up        4:00:00    2    idle hopper[011-012]
```

sinfo reports information about  
partitions

```
[vanilla@hopper ~]$ sinfo --partition debug
PARTITION AVAIL  TIMELIMIT  NODES  STATE NODELIST
debug      up       4:00:00    2    idle hopper[011-012]
```

The debug queues are intended  
for testing your programs.

And for interactive jobs.

```
[vanilla@hopper ~]$ sinfo --partition debug
PARTITION AVAIL  TIMELIMIT  NODES  STATE NODELIST
debug      up        4:00:00    2    idle hopper[011-012]
```



Name

```
[vanilla@hopper ~]$ sinfo --partition debug
PARTITION AVAIL  TIMELIMIT  NODES  STATE NODELIST
debug      up       4:00:00    2    idle hopper[011-012]
```



You can run a “job” for up to 4 hrs.

```
[vanilla@hopper ~]$ sinfo --partition debug
PARTITION AVAIL  TIMELIMIT  NODES  STATE NODELIST
debug      up        4:00:00    2    idle hopper[011-012]
```



There are two nodes in this partition.

```
[vanilla@hopper ~]$ sinfo --partition debug
PARTITION AVAIL  TIMELIMIT  NODES  STATE NODELIST
debug      up        4:00:00    2   idle hopper[011-012]
```



The names of the nodes in the  
partition

```
[vanilla@hopper ~]$ sinfo --partition debug
PARTITION AVAIL  TIMELIMIT  NODES  STATE NODELIST
debug      up        4:00:00    2   idle hopper[011-012]
```



The names of the nodes in the  
partition

```
[vanilla@hopper ~]$ sinfo --partition general
PARTITION AVAIL  TIMELIMIT  NODES  STATE NODELIST
general*   up    2-00:00:00      9  alloc hopper[001-009]
general*   up    2-00:00:00      1  idle  hopper010
```



Hopper001 through 009 are running jobs.

Hopper010 is waiting to be used.

```
[vanilla@hopper ~]$ hostname  
hopper  
[vanilla@hopper ~]$
```



Running on the Head Node.

The head node's name is "hopper".

```
[vanilla@hopper ~]$ hostname  
hopper
```

```
[vanilla@hopper ~]$ man hostname
```

```
[vanilla@hopper ~]$ hostname  
hopper
```

```
[vanilla@hopper ~]$ man hostname  
(‘q’ to quit)
```

```
[vanilla@hopper ~]$ man man  
(‘q’ to quit)
```

```
[vanilla@hopper ~]$ man sinfo
```

```
sinfo(1)  
Commands
```

```
Slurm  
sinfo(1)
```

## NAME

sinfo - View information about Slurm nodes and partitions.

## SYNOPSIS

sinfo [OPTIONS...]

## DESCRIPTION

sinfo is used to view partition and node information for a system running Slurm

## OPTIONS

-a, --all

Display information about all partitions. This causes information to be displayed about partitions that are configured as hidden and partitions that are unavailable to the user's group.

```
[vanilla@hopper ~]$ sinfo --all
```

| PARTITION | AVAIL | TIMELIMIT  | NODES | STATE | NODELIST                            |
|-----------|-------|------------|-------|-------|-------------------------------------|
| general*  | up    | 2-00:00:00 | 9     | alloc | hopper[001-009]                     |
| general*  | up    | 2-00:00:00 | 1     | idle  | hopper010                           |
| debug     | up    | 4:00:00    | 2     | idle  | hopper[011-012]                     |
| condo     | up    | 2-00:00:00 | 1     | down* | hopper045                           |
| condo     | up    | 2-00:00:00 | 3     | mix   | hopper[018-020]                     |
| condo     | up    | 2-00:00:00 | 16    | alloc | hopper[013-015,028-036,049-052]     |
| condo     | up    | 2-00:00:00 | 18    | idle  | hopper[016-017,021-027,037-044,053] |
| bugs      | up    | 7-00:00:00 | 2     | alloc | hopper[013-014]                     |
| pcnc      | up    | 7-00:00:00 | 1     | alloc | hopper015                           |
| pcnc      | up    | 7-00:00:00 | 1     | idle  | hopper016                           |
| pathogen  | up    | 7-00:00:00 | 1     | idle  | hopper017                           |
| tc        | up    | 7-00:00:00 | 3     | mix   | hopper[018-020]                     |
| tc        | up    | 7-00:00:00 | 2     | alloc | hopper[029-030]                     |
| tc        | up    | 7-00:00:00 | 5     | idle  | hopper[021-025]                     |
| gold      | up    | 7-00:00:00 | 2     | idle  | hopper[026-027]                     |
| fishgen   | up    | 7-00:00:00 | 1     | alloc | hopper028                           |
| neuro-hsc | up    | 7-00:00:00 | 6     | alloc | hopper[031-036]                     |
| neuro-hsc | up    | 7-00:00:00 | 8     | idle  | hopper[037-044]                     |
| cup-ecs   | up    | 7-00:00:00 | 2     | alloc | hopper[049-050]                     |
| tid       | up    | 7-00:00:00 | 1     | alloc | hopper051                           |
| biocomp   | up    | 7-00:00:00 | 1     | alloc | hopper052                           |
| chakra    | up    | 7-00:00:00 | 1     | idle  | hopper053                           |
| pna       | up    | 7-00:00:00 | 1     | down* | hopper045                           |

```
[vanilla@hopper ~]$ srun --partition debug hostname
```



Tell slurm to run a program  
on a compute node...

```
[vanilla@hopper ~]$ srun --partition debug hostname
```



Run the program on a  
compute node in the  
debug partition.

```
[vanilla@hopper ~]$ srun --partition debug hostname
```



The program  
to run.

```
[vanilla@hopper ~]$ srun --partition debug hostname  
srun: Account not specified in script or  
~/.default_slurm_account, using latest project  
You have not been allocated GPUs. To request GPUs,  
use the -G option in your submission script.  
hopper011
```

```
[vanilla@hopper ~]$ queue
```

**PD means programs  
that are waiting their  
turn.**

# Shows you what the slurm scheduler is doing right now.

Here we can see that user 'erowland' has a lot of programs waiting to run.

[illegible]

```
[vanilla@hopper ~]$ queue
```

The reason these jobs are not running is that 'erowland' is already using the maximum number of CPUs they are allowed.

```
[vanilla@hopper ~]$ squeue -t R --all
```

| JOBID | PARTITION | NAME     | USER     | ST | TIME       | NODES | NODELIST(REASON) |
|-------|-----------|----------|----------|----|------------|-------|------------------|
| 4405  | condo     | 2ndMA    | mfricke  | R  | 1-07:48:30 | 6     | hopper[031-036]  |
| 5208  | condo     | NN       | kgu      | R  | 5:48:49    | 1     | hopper015        |
| 5210  | condo     | NN       | kgu      | R  | 6:30:13    | 1     | hopper014        |
| 5209  | condo     | NN       | kgu      | R  | 6:31:13    | 1     | hopper013        |
| 5206  | condo     | NN       | kgu      | R  | 6:32:13    | 1     | hopper051        |
| 5207  | condo     | NN       | kgu      | R  | 6:32:13    | 1     | hopper052        |
| 5205  | condo     | NN       | kgu      | R  | 6:32:43    | 1     | hopper028        |
| 4595  | cup-ecs   | golConfi | aalasand | R  | 2-06:51:59 | 1     | hopper050        |
| 4594  | cup-ecs   | golConfi | aalasand | R  | 2-06:52:03 | 1     | hopper049        |
| 5120  | general   | jupyterh | jacobm   | R  | 11:45:47   | 1     | hopper007        |
| 4313  | general   | PRE      | erowland | R  | 1:17:29    | 2     | hopper[003-004]  |
| 5111  | general   | 1stMA    | mfricke  | R  | 11:15:28   | 2     | hopper[005-006]  |
| 5025  | general   | c2n      | jxzuo    | R  | 1:50       | 1     | hopper001        |
| 5024  | general   | c2n      | jxzuo    | R  | 31:28      | 1     | hopper002        |
| 5203  | general   | NN       | kgu      | R  | 6:37:50    | 1     | hopper009        |
| 5201  | general   | NN       | kgu      | R  | 6:38:14    | 1     | hopper008        |
| 4390  | tc        | UCsTpCyd | lepluart | R  | 2-15:18:18 | 3     | hopper[018-020]  |
| 5198  | tc        | NN       | kgu      | R  | 6:40:19    | 1     | hopper030        |
| 5196  | tc        | NN       | kgu      | R  | 6:40:31    | 1     | hopper029        |

```
[vanilla@hopper ~]$ srun --partition debug --ntasks 2 hostname  
srun: Account not specified in script or  
~/.default_slurm_account, using latest project  
You have not been allocated GPUs. To request GPUs, use the -G  
option in your submission script.  
hopper011  
hopper011
```

```
[vanilla@hopper ~]$ srun --partition debug --ntasks 2 hostname  
srun: Account not specified in script or  
~/.default_slurm_account, using latest project  
You have not been allocated GPUs. To request GPUs, use the -G  
option in your submission script.  
hopper011  
hopper011
```

You ran two **copies** of your program.

**ntasks** is the number of copies to run.

```
[vanilla@hopper ~]$ srun --partition debug --ntasks 8 hostname  
srun: Account not specified in script or  
~/.default_slurm_account, using latest project
```

```
hopper011
```

```
hopper011
```

```
hopper011
```

```
You have not been allocated GPUs. To request GPUs, use the -G  
option in your submission script.
```

```
hopper011
```

```
hopper011
```

```
hopper011
```

```
hopper011
```

```
hopper011
```

You ran eight **copies** of your program.

**ntasks** is the number of copies to run.

```
[vanilla@hopper ~]$ srun --partition debug --ntasks 8 hostname  
srun: Account not specified in script or  
~/.default_slurm_account, using latest project
```

hopper011

hopper011

hopper011

You have not been allocated GPUs. To request GPUs, use the -G option in your submission script.

hopper011

hopper011

hopper011

hopper011

hopper011

**By default, each task (copy of your program) is allowed to use one CPU.**

**Many programs are able to use more than one CPU at a time.**

```
[vanilla@hopper ~]$ srun --partition debug --ntasks 2 --cpus-per-task 2 hostname  
srun: Account not specified in script or ~/.default_slurm_account, using latest project  
You have not been allocated GPUs. To request GPUs, use the -G option in your submission  
script.
```

```
hopper011
```

```
hopper011
```

**Here we are telling SLURM to  
run 2 copies of our program  
and let each copy of our  
program use 2 CPUs.**

```
[vanilla@hopper ~]$ srun --partition debug --nodes 2 --ntasks-per-node 4 hostname  
srun: Account not specified in script or ~/.default_slurm_account, using  
latest project
```

```
hopper012
```

```
You have not been allocated GPUs. To request GPUs, use the -G option in  
your submission script.
```

```
hopper012
```

```
hopper011
```

```
hopper011
```

```
hopper012
```

```
hopper012
```

```
hopper011
```

```
hopper011
```

**Here we are telling SLURM to run 4  
copies of our program on 2 different  
compute nodes.**

**This is useful when our programs need  
a bigger share of the compute node.**

```
[vanilla@hopper ~]$ srun --partition debug --nodes 2  
--ntasks-per-node 2 --cpus-per-task 2 hostname  
srun: Account not specified in script or  
~/.default_slurm_account, using latest project  
hopper011  
You have not been allocated GPUs. To request GPUs, use  
the -G option in your submission script.  
hopper011  
hopper012  
hopper012
```

**And we can combine all three.**

```
[vanilla@hopper ~]$ srun --partition debug --mem 4G  
--nodes 2 --ntasks-per-node 2 --cpus-per-task 2  
hostname
```

```
srun: Account not specified in script or  
~/default_slurm
```

```
hopper012
```

```
hopper012
```

```
You have not been granted access to  
the -G option in
```

```
hopper011
```

```
Hopper011
```

**And we can specify how much  
memory we want.**

**--mem 4G means give me 4  
gigabytes of memory per node.**

```
[vanilla@hopper ~]$ srun --partition debug --mem 4G
--nodes 2 --ntasks-per-node 2 --cpus-per-task 2
hostname
srun: Account not specified in script or
~/default_slurm
hopper012
hopper012
You have not been granted access to the -G option in
hopper011
Hopper011
```

## Why does all this matter?

The purpose of SLURM is to provide you the hardware your programs need.

So you have to understand what those requirements are really well.

```
[vanilla@hopper ~]$ srun --partition debug --mem 4G  
--nodes 2 --ntasks-per-node 2 --cpus-per-task 2 hostname  
srun: Account not specified in script or  
~/ .default_slurm_account using latest project  
hopper012  
hopper012  
You have not been granted access to the partition debug  
the -G option is not supported  
hopper011  
Hopper011
```

- 1) Can my program use multiple CPUs?
- 2) How much memory does my program need?
- 3) Can my program use multiple compute nodes (MPI\*, GNU Parallel\*)?
- 4) Can my program use GPUs?

```
[vanilla@hopper ~]$ srun --partition debug --mem 4G  
--nodes 2 --ntasks-per-node 2 --cpus-per-task 2 hostname  
srun: Account not specified in script or  
~/default_slurm_account using latest project  
hopper012  
hopper012  
You have not been  
the -G option in  
hopper011  
Hopper011
```

This command is getting pretty long.

We can use **salloc** to avoid asking for the same resources every time we use **srun**.

```
[vanilla@hopper ~]$ salloc --partition debug --nodes 2  
--ntasks-per-node 2  
salloc: Account not specified in script or  
~/.default_slurm_account, using latest project  
salloc: Granted job allocation 5251  
salloc: Waiting for resource configuration  
salloc: Nodes hopper[011-012] are ready for job  
[vanilla@hopper ~]$
```

This command is getting pretty long.

We can use **salloc** to avoid asking for the same resources every time we use **srun**.

```
[vanilla@hopper ~]$ srun hostname
```

```
hopper012
```

```
hopper012
```

```
hopper011
```

```
You have not been allocated GPUs. To request GPUs, use  
the -G option in your submission script.
```

```
hopper011
```

```
[vanilla@hopper ~]$ srun hostname
```

```
hopper012
```

```
hopper011
```

```
hopper012
```

```
hopper011
```

```
[vanilla@hopper ~]$
```

Now we can use **srun** over and over without having to ask for a new hardware allocation each time.

```
[vanilla@hopper ~]$ exit
```

```
exit
```

```
salloc: Relinquishing job allocation 5251
```

Always type **exit** when you are done with the hardware.

Running salloc inside an allocation gets very confusing.

# Interactive vs Batch Mode

## Interactive Mode

- Everything so far has been interactive. You request hardware, run your program, and get the output on your screen right away.

## Batch Mode

- Most programs at an HPC center are run in “batch” mode.
- Batch mode means we write a shell script that the SLURM scheduler runs for us. The script requests hardware just like we did with `salloc` and then runs the commands in the script.
- Whatever would have been written to the screen is saved to a file instead.

```
[vanilla@hopper ~]$ git clone https://lobogit.unm.edu/CARC/workshops.git
Cloning into 'workshops'...
remote: Enumerating objects: 132, done.
remote: Counting objects: 100% (75/75), done.
remote: Compressing objects: 100% (43/43), done.
remote: Total 132 (delta 33), reused 74 (delta 32), pack-reused 57
Receiving objects: 100% (132/132), 57.58 KiB | 3.60 MiB/s, done.
Resolving deltas: 100% (51/51), done.
```

**Rather than make you write shell scripts lets just download some we wrote for this workshop...**

```
[vanilla@hopper ~]$ tree workshops
```

```
workshops/
├── intro_workshop
│   ├── code
│   │   ├── calcPiMPI.py
│   │   ├── calcPiSerial.py
│   │   └── vecadd
│   │       ├── Makefile
│   │       ├── vecadd_gpu.cu
│   │       ├── vecadd_mpi_cpu
│   │       ├── vecadd_mpi_cpu.c
│   │       ├── vecaddmpi_cpu.sh
│   │       └── vecadd_mpi_gpu.c
│   ├── data
│   │   ├── H20.gjf
│   │   └── step_sizes.txt
│   └── slurm
│       ├── calc_pi_array.sh
│       ├── calc_pi_mpi.sh
│       ├── calc_pi_parallel.sh
│       ├── calc_pi_serial.sh
│       ├── gaussian.sh
│       ├── hostname_mpi.sh
│       ├── vecadd_hopper.sh
│       ├── vecadd_xena.sh
│       ├── workshop_example2.sh
│       ├── workshop_example3.sh
│       └── workshop_example.sh
└── README.md
```

**Run tree to see how the workshops directories are organized...**

```
[vanilla@hopper ~]$ tree workshops
```

```
workshops/
├── intro_workshop
│   ├── code
│   │   ├── calcPiMPI.py
│   │   ├── calcPiSerial.py
│   │   └── vecadd
│   │       ├── Makefile
│   │       ├── vecadd_gpu.cu
│   │       ├── vecadd_mpi_cpu
│   │       ├── vecadd_mpi_cpu.c
│   │       ├── vecaddmpi_cpu.sh
│   │       └── vecadd_mpi_gpu.c
│   ├── data
│   │   ├── H20.gjf
│   │   └── step_sizes.txt
│   └── slurm
│       ├── calc_pi_array.sh
│       ├── calc_pi_mpi.sh
│       ├── calc_pi_parallel.sh
│       ├── calc_pi_serial.sh
│       ├── gaussian.sh
│       ├── hostname_mpi.sh
│       ├── vecadd_hopper.sh
│       ├── vecadd_xena.sh
│       ├── workshop_example2.sh
│       ├── workshop_example3.sh
│       └── workshop_example.sh
└── README.md
```

Run **tree** to see how the workshops directories are organized...

The workshop files are divided into “code”, “slurm”, and “data” directories.

```
[vanilla@hopper intro_workshop]$ pwd
/users/vanilla/workshops/intro_workshop
[vanilla@hopper intro_workshop]$ cat slurm/workshop_example.sh
#!/bin/bash
#SBATCH --partition debug
#SBATCH --ntasks 4
#SBATCH --time 00:05:00
#SBATCH --job-name ws_example
#SBATCH --mail-user your_username@unm.edu
#SBATCH --mail-type ALL
```

```
hostname
```

Let's take a look at the **workshop\_example.sh** script in the slurm directory...

```
[vanilla@hopper intro_workshop]$ sbatch slurm/workshop_example.sh
sbatch: Account not specified in script or ~/.default_slurm_account,
using latest project
Submitted batch job 5252
[vanilla@hopper intro_workshop]$
```

We **submit** our slurm  
shell script with the  
sbatch command.

```
[vanilla@hopper intro_workshop]$ sbatch slurm/workshop_example.sh  
sbatch: Account not specified in script or ~/.default_slurm_account,  
using latest project  
Submitted batch job 5252  
[vanilla@hopper intro_workshop]$
```


Notice that the only output we get is a job id.

This indicates that the script was successfully sent to the scheduler.

The commands in the script will run as soon as the hardware requested is available.

We **submit** our slurm shell script with the sbatch command.

# Workflow



Compute Node 01

Compute Node 02


Compute Node 03

Compute Node 04

Compute Node 05


Shared filesystems – All nodes can access the same programs and write output

# Workflow




Shared filesystems – All nodes can access the same programs and write output

# Workflow



Shared filesystems – All nodes can access the same programs and write output


# Workflow



Shared filesystems – All nodes can access the same programs and write output

# Workflow

We need something in the script to run the program on all the nodes. E.g. srun.



Shared filesystems – All nodes can access the same programs and write output

```
[vanilla@hopper intro_workshop]$ ls  
code  data  pbs  slurm  slurm-5252.out
```

The **hostname** command is very fast so everyone's job should finish in a few seconds.

When it is finished you will have a new file named `slurm-{your job id}.out`.



```
[vanilla@hopper intro_workshop]$ ls  
code  data  pbs  slurm  slurm-5252.out
```



**When it is finished you will have a new file named slurm-{your job id}.out.**

```
[vanilla@hopper intro_workshop]$ cat slurm-5252.out  
hopper011
```

```
[vanilla@hopper intro_workshop]$ ls  
code  data  pbs  slurm  slurm-5252.out
```



When it is finished you will have a new file named `slurm-{your job id}.out`.

```
[vanilla@hopper intro_workshop]$ cat slurm-5252.out  
hopper011
```

Why did it only run the program once instead of 4 times?

```
[vanilla@hopper intro_workshop]$ sbatch slurm/workshop_example1.sh
sbatch: Account not specified in script or ~/.default_slurm_account,
using latest project
Submitted batch job 5252
[vanilla@hopper intro_workshop]$
```

**Take a look at the  
output file.**

```
[vanilla@hopper intro_workshop]$ module load miniconda3  
[vanilla@hopper intro_workshop]$ conda create -n numpy numpy
```

Wait a while – introduce yourselves to your neighbor...

Conda allows you to install software into your home directory. In this case we need the numerical python libraries for calcPiSerial.py

**Let's experiment with a program that does slightly more than print the hostname.**

```
[vanilla@hopper intro_workshop]$source activate numpy
[vanilla@hopper intro_workshop]$srun --partition debug python
code/calcPiSerial.py 10
srun: Using account 2016199 from ~/.default_slurm_account
You have not been allocated GPUs. To request GPUs, use the -G
option in your submission script.
Pi = 3.14242598500109870940, (Diff=0.000833333141130559341)
(calculated in 0.000005 secs with 10 steps)
```

**Activate the numpy environment and  
Run calcPiSerial.py on a compute node.**

**For our example program the more steps it takes the  
more accurate it is, but the longer it takes.**

```
[vanilla@hopper intro_workshop]$ sbatch slurm/calc_pi_serial.sh  
sbatch: Using account 2016199 from ~/.default_slurm_account
```

```
Submitted batch job 5263
```

```
vanilla@hopper:~/workshops/intro_workshop$ squeue -me
```

| JOBID | PARTITION | NAME     | USER    | ST | TIME | NODES | NODELIST(REASON) |
|-------|-----------|----------|---------|----|------|-------|------------------|
| 5263  | debug     | calc_pi_ | vanilla | R  | 0:44 | 1     | hopper011        |

Edit `slurm/calc_pi_serial.sh`.

Change the email address to your address and submit the script.

Then enter **squeue --me** to see the job status.

Take a look at the job output.

# Parallelism – Embarrassingly Parallel

- Embarrassingly parallel (Cleve Moler) are problems that are really really easy to speed up with more CPUs.
- The most common example is that you have a program that runs in serial and takes some input file, processes it, and produces some output.
- The problem is that you have 1,000 of the input files and want to run your program on each one.



# Parallelism – Embarrassingly Parallel

This is “embarrassing”  
because all you have to do  
is run 1,000 copies of your  
program on 1,000 CPUs  
each with a different input  
file and you are done.



# SLURM ARRAYS

- One way to run the 1,000 copies of your program on 1,000 different inputs would be to write 1,000 slurm scripts each specifying a different input to your program and then sbatch submit them all. (this would work but there are better ways).
- SLURM arrays are used to schedule a lot of jobs with one slurm script.

```
[vanilla@hopper intro_workshop]$ nano slurm/calc_pi_array.sh
```

```
#!/bin/bash
```

```
#SBATCH --partition debug
```

```
#SBATCH --ntasks 1
```

```
#SBATCH --time 00:05:00
```

```
#SBATCH --job-name calc_pi_array
```

```
#SBATCH --mail-user your_username@unm.edu
```

```
#SBATCH --mail-type ALL
```

```
#SBATCH --array=1-12%3
```

```
echo "$HOSTNAME - $SLURM_ARRAY_TASK_ID"
```

```
module load miniconda3
```

```
source activate numpy
```

```
NUM_STEPS="${SLURM_ARRAY_TASK_ID}0000"
```

```
echo "Calculating pi with $NUM_STEPS..."
```

```
cd $SLURM_SUBMIT_DIR
```

```
python code/calcPiSerial.py $NUM_STEPS
```

**Requires some  
annoying bash  
scripting.**

**\$something means get  
the value of the  
variable “something”**

```
[vanilla@hopper intro_workshop]$ nano slurm/calc_pi_array.sh
```

```
#!/bin/bash
```

```
#SBATCH --partition debug
```

```
#SBATCH --ntasks 1
```

```
#SBATCH --cpus-per-task 3
```

```
#SBATCH --time 00:05:00
```

```
#SBATCH --job-name calc_pi_array
```

```
#SBATCH --mail-user your_username@unm.edu
```

```
#SBATCH --mail-type ALL
```

```
#SBATCH --array=1-12%3
```

```
echo "$HOSTNAME - $SLURM_ARRAY_TASK_ID"
```

```
module load miniconda3
```

```
source activate numpy
```

```
NUM_STEPS="${SLURM_ARRAY_TASK_ID}0000"
```

```
echo "Calculating pi with $NUM_STEPS..."
```

```
cd $SLURM_SUBMIT_DIR
```

```
python code/calcPiSerial.py $NUM_STEPS
```

**--array says**

- 1) run 12 separate jobs**
- 2) Store the count of the job in the variable `SLURM_ARRAY_TASK_ID`**

**Notice there is no `srun`.**

**Why not?**

```
[vanilla@hopper intro_workshop]$ sbatch slurm/calc_pi_serial.sh  
sbatch: Using account 2016199 from ~/.default_slurm_account
```

```
Submitted batch job 5263
```

```
vanilla@hopper:~/workshops/intro_workshop$ squeue -me
```

| JOBID | PARTITION | NAME     | USER    | ST | TIME | NODES | NODELIST(REASON) |
|-------|-----------|----------|---------|----|------|-------|------------------|
| 5263  | debug     | calc_pi_ | vanilla | R  | 0:44 | 1     | hopper011        |

Submit the array script.

Then enter **squeue --me** to see the job status.

Take a look at the job output. (How many output files do you have?)

JOB arrays are OK or very simple inputs like programs that take a single file as input. But even passing in a value takes some annoying variable manipulation.


GNU Parallel is much more sophisticated it can take inputs in all sorts of ways. We will look at just 3 ways.

To access GNU parallel enter **module load parallel**

Let's experiment with parallel interactively...

**\*NOTE: we don't use srun to run parallel.**

# GNU Parallel



Has been around for a very long time and has lots and lots of great features.

But basically it creates a job for every input it receives. The inputs can be specified in the command, read from a file, or be the output of another program.

It also remembers which jobs have finished and which still need to be run. So when you run out of time and resubmit it will automatically pick up where it left off.

```
[vanilla@hopper intro_workshop]$ salloc --partition debug --ntasks 2
salloc: Using account 2016199 from ~/.default_slurm_account
salloc: Granted job allocation 5275
salloc: Waiting for resource configuration
salloc: Nodes hopper011 are ready for job
```

```
$ LANG=C
```

```
$ parallel python code/calcPiSerial.py ::: 10 20 30 40
```

```
Pi = 3.14180098689309428295, (Diff=0.00020833330330116695)
(calculated in 0.000006 secs with 20 steps)
Pi = 3.14164473692265744376, (Diff=0.00005208333286432776)
(calculated in 0.000008 secs with 40 steps)
Pi = 3.14242598500109870940, (Diff=0.000833333141130559341)
(calculated in 0.000006 secs with 10 steps)
Pi = 3.14168524617974842528, (Diff=0.00009259258995530928)
(calculated in 0.000012 secs with 30 steps)
```

```
[vanilla@hopper intro_workshop]$ seq 10 10 100
```

```
10  
20  
30  
40  
50  
60  
70  
80  
90  
100
```

**GNU Parallel can read the output of other programs and use them as inputs to your program.**

**Here a copy of calc pi is run for each row in the output of **seq****

```
[vanilla@hopper intro_workshop]$ seq 10 10 100 | parallel python code/calcPiSerial.py  
Pi = 3.14180098689309428295, (Diff=0.00020833330330116695) (calculated in 0.000007  
secs with 20 steps)  
Pi = 3.14242598500109870940, (Diff=0.000833333141130559341) (calculated in 0.000006  
secs with 10 steps)  
Pi = 3.14168524617974842528, (Diff=0.00009259258995530928) (calculated in 0.000007  
secs with 30 steps)  
etc
```

```
[vanilla@hopper intro_workshop]$ find -name *.sh
./slurm/calc_pi_array.sh
./slurm/calc_pi_mpi.sh
./slurm/calc_pi_parallel.sh
./slurm/calc_pi_serial.sh
./slurm/gaussian.sh
./slurm/hostname_mpi.sh
etc
```

```
$ find -name *.sh | parallel wc -l
7 ./code/vecadd/vecaddmpi_cpu.sh
19 ./slurm/calc_pi_array.sh
15 ./slurm/calc_pi_mpi.sh
20 ./slurm/calc_pi_parallel.sh
14 ./slurm/calc_pi_serial.sh
16 ./slurm/gaussian.sh
15 ./slurm/hostname_mpi.sh
etc
```

A common application is to use **find** to produce a list of paths with some extension.

Then parallel runs some program on each path.

In this case **wc -l** counts the lines in a file. In some real CARC examples the input files are phylogenetic trees, graphs, neuroimages, or CT scans.

```
[vanilla@hopper intro_workshop]$ exit  
exit  
salloc: Relinquishing job allocation 5275
```

**Don't forget to exit your  
salloc allocation.**

```
(numpy)[vanilla@hopper intro_workshop]$ cat slurm/calc_pi_parallel.sh
#!/bin/bash
#SBATCH --partition debug
#SBATCH --nodes 2
#SBATCH --ntasks-per-node 4
#SBATCH --time 00:05:00
#SBATCH --job-name calc_pi_parallel
#SBATCH --mail-user your_username@unm.edu
#SBATCH --mail-type ALL

module load parallel
module load miniconda3
source activate numpy

LANG=C
cd $SLURM_SUBMIT_DIR
parallel --sshloginfile $PBS_NODEFILE \
--env PATH \
--workdir $SLURM_SUBMIT_DIR \
"hostname; python code/calcPiSerial.py {}" ::: data/step_sizes.txt
```

Take a look at  
slurm/calc\_pi\_parallel.sh.

In this example parallel  
reads the parameters from  
a file and runs a copy of  
calcPiSerial.py on each  
row.



```
(numpy)$ sbatch slurm/calc_pi_parallel.sh  
sbatch: Using account 2016199 from ~/.default_slurm_account  
Submitted batch job 5276
```


**Submit the job, check it's progress with `squeue --me`, and take a look at the output.**

# Parallelism – Coupled Parallelism


- Coupled problems are those where the CPUs need to work together to solve a problem by communicating with each other.
- Many commercial and research programs designed to run on HPC systems like CARC use a library called the message passing interface (MPI) to do this.
- We have written an MPI version of our python pi calculator to demonstrate.



# Serial Program to Calculate $\pi$



# Parallel Program to Calculate $\pi$



# MPI: Message Passing Interface

When programs need to run on many processors but also communicate with one another.

Here the parallel version of calcPi needs to communicate the partial sums computed by each process so they can all be added up.

To communicate we will use the MPI library:

```
module load miniconda3  
conda create -n mpi_numpy mpi mpi4py numpy
```

```

import time
import sys
import numpy as np # Value of PI to compare to

##### SETUP MPI - START #####
from mpi4py import MPI      #Import the MPI library
comm = MPI.COMM_WORLD      #Communication framework
root = 0                    #Root process
rank = comm.Get_rank()      #Rank of this process
num_procs = comm.Get_size() #Total number of processes
##### END #####

#Distributed function to calculate pi
def Pi(num_steps):
    step = 1.0 / num_steps
    sum = 0
    for i in range(rank, num_steps, num_procs): # Divide sum among
processes
        x = (i + 0.5) * step
        sum = sum + 4.0 / (1.0 + x * x)
    mypi = step * sum

    # Get that partial sums from all the processes, add them up, and give
to the root process
    pi = comm.reduce(mypi, MPI.SUM, root)
    return pi

```

```

#Main function
# Check that the caller gave us the number of steps to use
if len(sys.argv) != 2:
    print("Usage: ", sys.argv[0], " <number of steps>")
    sys.exit(1)

num_steps = int(sys.argv[1],10);

#Broadcast number of steps to use to the other processes
comm.bcast(num_steps, root)

# Call function to calculate pi
start = time.time() #Start timing
pi = Pi(num_steps) # Call the function that calculates pi
end = time.time() # End timing

# If we are the root process then print our estimation of pi,
# the difference from numpy's value, and how long it took
print("Pi = %.20f, (Diff=%.20f) (calculated in %f secs with %d
steps)" %(pi, pi-np.pi, end - start, num_steps))

```

```
#!/bin/bash
#SBATCH --partition debug
#SBATCH --nodes 2
#SBATCH --ntasks-per-node 4
#SBATCH --time 00:05:00
#SBATCH --job-name calc_pi_mpi
#SBATCH --mail-user your_username@unm.edu
#SBATCH --mail-type ALL

module load miniconda3
source activate mpi_numpy

cd $SLURM_SUBMIT_DIR
srun --mpi=pmi2 python code/calcPiMPI.py 1000000000
```

`sbatch slurm/calc_pi_mpi.sh`

```
srun --mpi=pmi2 python code/calcPiMPI.py 1000000000
```

## srun understands MPI programs!

If you ever used mpirun or mpiexec you had to provide a lot of parameters to describe how many compute nodes you had and what their names are, etc.

But srun is part of SLURM so it already knows all that.

The only thing you have to specify is the communication library to use. In our case “pmi2”.

## Experiment

Run `calc_pi_mpi.sh`.

Vary the number of tasks it uses.

Use `squeue` to monitor the state of your job,

Look at your output files.

What is the relationship between the number of tasks and how fast it calculates pi?

# Useful Slurm Commands

|                                  |                                             |
|----------------------------------|---------------------------------------------|
| <code>squeue --me --long</code>  | shows information about jobs you submitted  |
| <code>squeue --me --start</code> | shows when slurm expects your job to start  |
| <code>scancel jobid</code>       | Cancels a job                               |
| <code>scancel --u \$USER</code>  | Cancels all your jobs                       |
| <code>sacct</code>               | Shows your job history                      |
| <code>seff jobid</code>          | Shows how efficiently the hardware was used |